

## TRANSTAR SYNTHETIC FLUIDS



PART #	PRODUCT	DESCRIPTION	SIZE
M465AL	ALLISON ATF	Transtar Heavy Duty Multi-Vehicle fluid is made with premium quality base oils and additives. Recommended for use in on- and off-road commercial vehicles that utilize Allison, Ford, MAN, MB, Volth and ZF synthetic high-viscosity ATF.	1 Gallon 2.5 Gallon
M465MVCVT	MULTI VEHICLE CVT	This Multi-Vehicle CVT Transmission Fluid is designed to meet the performance requirements of a wide variety of vehicles equipped with push-belt CVTs and chain CVTs equipped with a torque converter.	1 Quart 2.5 Gallon 55 Gallon
M465MVDEX3	SPECIAL BLEND DEX III	The automatic transmission fluid is made with premium-quality base oils and additives. It is recommended and approved for all automatic transmissions which use Dexron III, Ford Mercon and Allison C4 fluids.	1 Quart 2.5 Gallon 55 Gallon
M465MVHV	MULTI VEHICLE HV	This High-Viscosity Multi-Vehicle ATF is suitable for use in vehicles that use Dexron II/III, Mercon V, ATF +3/4, and other high-viscosity fluids. Recommended for use in on- and off-road commercial vehicles that utilize Allison (C-4/TES-389/TES-295), MAN, MB, Voith, Volvo and ZF high-viscosity ATF.	1 Quart 2.5 Gallon 55 Gallon
M465MVLV	MULTI VEHICLE LV	This Low-Viscosity Multi-Vehicle ATF is suitable for use in vehicles that use ATF-J3, Dexron VI, DW-1, Matic-S, Mercon LV, SP-IV, SPH-IV, WS, FZ, ZF6 and ZF8.	1 Quart 2.5 Gallon 55 Gallon
M465TES	ALLISON ATF	This Automatic Transmission Fluid is made with premium-quality base oil and additives. Recommended for use in on- and off-road commercial vehicles that utilize Allison TES 295, Ford, MAN, MB, Voith and ZF synthetic high-viscosity ATF.	1 Gallon 2.5 Gallon
M465MVULV	TRANSTAR MULTI VEHICLE ULV	This Ultra Low Viscosity Multi-Vehicle ATF is suitable for use in vehicles that use AISIN: AW-2, FORD: Mercon ULV, GM: Dexron ULV, MERCEDES: 236.15, 236.16, MAZDA: A7, NISSAN: Matic P, AUDI: G 043 001 A2 and G 060 540 A2. Be sure to check the owner's manual.	1 Quart 2.5 Gallon

Part Number Suffix: Add -1G for 1 Gallon, -2.5 for 2.5 Gallon, -5 for 5-Gallon Bucket, -55 for 55-Gallon Drum



## OE & OTHER BRAND FLUIDS (IN QUARTS UNLESS OTHERWISE SPECIFIED)

MANUFACTURER	PART #	TRANSTAR EQUIVALENT	DESCRIPTION
Lubegard	M465TF	Lubegard Complete Full Synthetic ATF	A world-class replacement for synthetic low-viscosity ATF. Formulated with LXE technology to meet OEM requirements for shear stability, long-term frictional stability, superior shift quality and anti-shudder properties.
	M465CVTB	Lubegard Complete Full Synthetic CVT	A world-class fluid formulated for outstanding performance and efficiency in meeting or exceeding OEM requirements for continuously variable transmissions.
	M465CVTB-G	Lubegard Complete Full Synthetic CVT	A world-class fluid formulated for outstanding performance and efficiency in meeting or exceeding OEM requirements for continuously variable transmissions.
AC Delco	10-9394/10-9243	AC Delco DexVI	Full synthetic transmission fluid for GM transmission models 2006 and newer calling for Dexron-VI, III or IIE.
	10-9395/10-9244	AC Delco DexVI (1 Gallon)	Full synthetic transmission fluid, 1 gallon.
	M465DEXULV	AC Delco Ultra-Low Viscosity	Ultra-low viscosity and fully synthetic transmission fluid designed for 10-speed transmissions.
Mobil 1	M465MB1-LV	Mobil 1 Synthetic LV ATF HP	Recommended for use in modern high-performance vehicles requiring DEXRON HP ATF DEXRON.
Mopar	M465-P4	Mopar ATF+4 Traditional Transmission Fluid	The approved automatic transmission fluid for all vehicles factory filled with ATF+4.
	M465-ASRC	Mopar Traditional Transmission Fluid	Formulated as an exceptionally high performance lubricant for use in AS66RC, AS68RC and AS69RC slip-controlled lock-up automatic transmissions.
	M465PCVT	Mopar CVT Fluid	For use in specific Chrysler/Jeep/Dodge CVTs.
	M465BA1	Mopar Traditional Transmission Fluid	Designed for use in 8-speed (8HP70) and 9-speed (948TE) automatic transmissions.
Motorcraft	M465F10-1	Mercon Low Viscosity	Recommended by Ford Motor Company for use in Ford, Lincoln and Mercury vehicles that require MERCON LV type fluid OEM product.
	M465QULV-1	Mercon Ultra-Low Viscosity	Manufactured with high-viscosity index, premium-quality, hydroprocessed base oils and specially designed performance additives.
Idemitsu	M465M5	Idemitsu ATF Type M	Engineered for Mazda Automatic M-V (M5) specification.
	M465S	Idemitsu ATF Type S	Engineered for Nissan/Infiniti Matic-D/J/S specification.
	M465DW1	Idemitsu ATF Type H Plus	Engineered for Honda/Acura DW-1 & Z-1 specification.
	M465SHP	Idemitsu ATF Type HP	Engineered for Subaru ATF specification.
	M465T-IV	Idemitsu ATF Type TLS	Engineered for Toyota/Lexus/Scion T-IV specification.
	M465TWS	Idemitsu ATF Type TLS-LV	Engineered for Toyota/Lexus/Scion WS specification.
	M465SP-III	Idemitsu ATF Type HK	Engineered for Hyundai/Kia/Mitsubishi SP-III specification.
	M465HK4	Idemitsu ATF Type HK 4	Engineered for Hyundai/Kia/Mitsubishi SP-IV specification.
	M465NCVT	Idemitsu CVTF Type N	Engineered for Nissan/Infiniti NS-2 specification.
	M465N3	Idemitsu CVTF Type N3	Engineered for Nissan/Infiniti NS-3 specification.
	M465TLSFE	Idemitsu CVTF Type TLS-FE	Engineered for Toyota/Lexus/Scion Toyota CVT FE specification.
	M465SB2-1	Idemitsu CVTF Type SB2	Engineered for Subaru CVTF II specification.
	M465HCF2	Idemitsu CVTF Type H2	Engineered for the latest generation of continuously variable transmissions where HCF-2CVT fluid is specified.
ZF	M465ZF5-1	ZF Lifeguard Fluid 5 ATF	Oil type - Fluid 5.
	M465ZF6-1	ZF Lifeguard Fluid 6 ATF	Oil type - Fluid 6.
	M465ZF8-1	ZF Lifeguard Fluid 8 ATF	Oil type - Fluid 8.
	M465ZF9-1	ZF TE-ML11 ATF	For use in ZF brand model 9HP48. Must shake vigorously before adding.

